



SPORTS

DOMINIQUE 01

Sneaker with optimal cushioning and comfort

Dominique is a trendy sneaker, adapted to the needs of many professionals. This closed shoe provides maximum protection and fits perfectly. The air unit and the removable foam footbed provides optimal cushioning and gives great comfort. The slip-resistant outsole and the breathable lining completes this ultimate professional sneaker to serve any in need of comfort during and beside their working day.

Upper	Mesh, Printed Action Leather
Outsole	PU/Rubber
Toecap	
Midsole	
Lining	3D-Mesh, Mesh
Footbed	SJ foam footbed
Safety category	EN ISO 20347 - O1 / ESD, SRC
Sample weight	410 gr.
Size range	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 / CM 23.0-31.0



OXYGRIP / SJ GRIP
Rubber outsoles with Oxytraction® technology provide excellent traction on both dry and wet floors and meet SRC (SRA+ SRB) standards.



ELECTROSTATIC DISCHARGE (ESD)
ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 35 MegaOhm.



SJ FOAM
Removable comfortable antistatic footbed providing fit, guidance and optimum shock absorption in heel and forefoot. Breathable and moisture absorbing.



SRC SLIP RESISTANCE
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



BREATHABLE UPPER
Increased moisture and temperature management for extended wearer comfort.

DOMINIQUE 01

Industries:

Catering, Cleaning, Food & beverages, Medical

Environments:

Extreme slippery surfaces, Uneven surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.



	Description	Measure unit	Result	EN ISO 20347
Upper	Mesh, Printed Action Leather			
	Upper: permeability to water vapor	mg/cm ² /h	1.1	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	16.8	≥ 15
Lining	3D-Mesh, Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	67.9	≥ 2
	Lining: water vapor coefficient	mg/cm ²	543	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	PU/Rubber			
	Outsole abrasion resistance (volume loss)	mm ³	120	≤ 150
	Outsole slip resistance SRA: heel	friction	0.29	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.33	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.21	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.23	≥ 0.18
	Antistatic value	MegaOhm	NA	0.1 - 1000
	ESD value	MegaOhm	73.6	0.1 - 100
	Heel energy absorption	J	36	≥ 20
Toecap	Impact resistance toecap (clearance after impact 100J)	mm	NA	≥ 14
	Compression resistance toecap (clearance after compression 10kN)	mm	NA	≥ 14
	Impact resistance toecap (clearance after impact 200J)	mm	NA	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	NA	≥ 14

Our shoes are constantly evolving, the technical data above may change.
All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size: 41