

SAFETY JOGGER

PROFESSIONAL



MOVE

EVA 01

Sporty look, great comfort

Upper	Printed Action Leather
Outsole	EVA, Rubber
Toecap	
Midssole	
Lining	Coolmax Mesh
Footbed	Coolmax Mesh
Safety category	EN ISO 20347 - O1 / ESD, SRC
Sample weight	0.270 gr.
Size range	EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 / CM 23.0-27.0



ELECTROSTATIC DISCHARGE (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 35 MegaOhm.



COOLMAX® LINING

Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



REMOVABLE INSOLE

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.

SAFETY JOGGER

PROFESSIONAL

MOVE

EVA 01

Industries:

Catering, Cleaning, Food & beverages, Medical, Uniform

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20347
Upper	Printed Action Leather			
	Upper: permeability to water vapor	mg/cm ² /h	1.3	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	17.4	≥ 15
Lining	Coolmax Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	14.5	≥ 2
	Lining: water vapor coefficient	mg/cm ²	116.1	≥ 20
Footbed	Coolmax Mesh			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	EVA, Rubber			
	Outsole abrasion resistance (volume loss)	mm ³	77	≤ 150
	Outsole slip resistance SRA: heel	friction	0.43	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.53	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.13	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.26	≥ 0.18
	Antistatic value	MegaOhm	88	0.1 - 1000
	ESD value	MegaOhm	22	0.1 - 100
	Heel energy absorption	J	29	≥ 20
Toecap	Impact resistance toecap (clearance after impact 100J)	mm	N/A	≥ 13
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	≥ 13
	Impact resistance toecap (clearance after impact 200J)	mm	N/A	≥ 13
	Compression resistance toecap (clearance after compression 15kN)	mm	N/A	≥ 13

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size:
37