

SAFETY JOGGER

PROFESSIONAL



MOVE

LILIA OB

Elegant and casual

| | |
|-----------------|--|
| Upper | Printed Action Leather |
| Outsole | EVA, Rubber |
| Toecap | |
| Midssole | |
| Lining | Coolmax Mesh |
| Footbed | Coolmax Mesh |
| Safety category | EN ISO 20347 - OB / ESD, A, SRC, E |
| Sample weight | 0.236 gr. |
| Size range | EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 / CM 23.0-27.0 |



ELECTROSTATIC DISCHARGE (ESD)

ESD provides the controlled discharge of electrostatic energy that can damage electronic components and avoids risks of ignition resulting from electrostatic charges. Volume resistance between 100 KiloOhm and 35 MegaOhm.



COOLMAX® LINING

Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



REMOVABLE INSOLE

Renew your insole at a regular base or use your own orthopedic insoles for a higher comfort.

SAFETY JOGGER

PROFESSIONAL

MOVE

LILIA OB

Industries:

Catering, Cleaning, Food & beverages, Medical

Environments:

Dry environment, Extreme slippery surfaces

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

| | Description | Measure unit | Result | EN ISO 20347 |
|----------------|--|-----------------------|--------|--------------|
| Upper | Printed Action Leather | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | 1.4 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 15.5 | ≥ 15 |
| Lining | Coolmax Mesh | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | 14.5 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | 116.1 | ≥ 20 |
| Footbed | Coolmax Mesh | | | |
| | Footbed: abrasion resistance | cycles | 400 | ≥ 400 |
| Outsole | EVA, Rubber | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 111 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.43 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.53 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.13 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.26 | ≥ 0.18 |
| | Antistatic value | MegaOhm | 88 | 0.1 - 1000 |
| | ESD value | MegaOhm | 22 | 0.1 - 100 |
| | Heel energy absorption | J | 29.0 | ≥ 20 |
| Toecap | Impact resistance toecap (clearance after impact 100J) | mm | N/A | ≥ 13 |
| | Compression resistance toecap (clearance after compression 10kN) | mm | N/A | ≥ 13 |
| | Impact resistance toecap (clearance after impact 200J) | mm | N/A | ≥ 13 |
| | Compression resistance toecap (clearance after compression 15kN) | mm | N/A | ≥ 13 |

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size:
37