

SAFETY JOGGER

INDUSTRIAL

SEASONAL

ALASKA S3

Leather safety boot with warm lining

Upper	Pull-up Action Leather
Outsole	PU/PU
Toecap	Steel
Midsole	Steel
Lining	Teddy
Footbed	Teddy
Safety category	EN ISO 20345 - S3 / SRC, CI
Sample weight	0.853 gr.
Size range	EU 38-47 / UK 5.0-12.0 / US 5.5-13.0 / CM 25.0-31.0



BRN



S3

S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



SRC SLIP RESISTANCE

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



COLD INSULATED (CI)

Cold insulated (CI) safety shoes keep your feet warm. They are worn in cold environments.



WARM LINING

Keeps your feet warm and dry in cold environments.



WATER RESISTANT UPPER (WRU)

Prevents penetration of water if not permanently exposed to high levels.



ANTISTATIC

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm

SAFETY JOGGER
WORKS

INDUSTRIAL PROFESSIONAL TACTICAL

www.pls-shop.co.uk

PLS

ENGINEERED
IN EUROPE

SAFETY JOGGER

INDUSTRIAL

SEASONAL

ALASKA S3

Industries:

Automotive, Chemical, Construction, Industry, Mining, Oil & Gas

Environments:

Cold environment, Muddy environment, Snowy and icy, Uneven surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Pull-up Action Leather			
	Upper: permeability to water vapor	mg/cm ² /h	7.1	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	64	≥ 15
Lining	Teddy			
	Lining: permeability to water vapor	mg/cm ² /h	1206	≥ 2
	Lining: water vapor coefficient	mg/cm ²	964.8	≥ 20
Footbed	Teddy			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm ³	85.1	≤ 150
	Outsole slip resistance SRA: heel	friction	0.40	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.42	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.19	≥ 0.18
	Antistatic value	MegaOhm	108.7	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	30	≥ 20
Toecap	Steel			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	≥ 14
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	≥ 14
	Impact resistance toecap (clearance after impact 200J)	mm	15.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	15.0	≥ 14

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size:
41