

SAFETY JOGGER

TACTICAL



TACTICAL

ARMOUR 02

Mid-cut allround tactical boot

| | |
|-----------------|---|
| Upper | Waterproof Leather |
| Outsole | EVA/Rubber |
| Toecap | |
| Midsole | |
| Lining | Coolmax Mesh, Sympatex Membrane |
| Footbed | SJ foam footbed |
| Safety category | EN ISO 20347 - O2 / SRC, WR, HI, CI, FO, HRO |
| Sample weight | 0.535 gr. |
| Size range | EU 36-48 / UK 3.5-13.0 / US 4.0-13.5 / CM 23.5-31.5 |



BLK



SYMPATEX® LINING

Keeps your feet dry and comfortable in all weather conditions.



COOLMAX® LINING

Coolmax® technology was originally developed for athletes. The material transports moisture and sweat, so that the body stays dry. We found it extremely suitable for people who work hard for hours every day too.



WATERPROOF (WR)

Waterproof footwear prevents liquids to enter into the shoe.



HEAT RESISTANT OUTSOLE (HRO)

The outsole resists high temperatures up to 300°C.



ANTISTATIC

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



OIL & FUEL RESISTANT

The outsole is resistant against oil and fuel.

SAFETY JOGGER
WORKS

INDUSTRIAL PROFESSIONAL TACTICAL

www.pls-shop.co.uk

PLS

ENGINEERED
IN EUROPE

SAFETY JOGGER

TACTICAL



TACTICAL

ARMOUR 02

Industries:

Tactical, Uniform

Environments:

Muddy environment, Uneven surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.



| | Description | Measure unit | Result | EN ISO 20347 |
|----------------|--|-----------------------|--------|--------------|
| Upper | Waterproof Leather | | | |
| | Upper: permeability to water vapor | mg/cm ² /h | 4.2 | ≥ 0.8 |
| | Upper: water vapor coefficient | mg/cm ² | 39 | ≥ 15 |
| Lining | Coolmax Mesh, Sympatex Membrane | | | |
| | Lining: permeability to water vapor | mg/cm ² /h | 3.4 | ≥ 2 |
| | Lining: water vapor coefficient | mg/cm ² | 27 | ≥ 20 |
| Footbed | SJ foam footbed | | | |
| | Footbed: abrasion resistance | cycles | 400 | ≥ 400 |
| Outsole | EVA/Rubber | | | |
| | Outsole abrasion resistance (volume loss) | mm ³ | 68 | ≤ 150 |
| | Outsole slip resistance SRA: heel | friction | 0.33 | ≥ 0.28 |
| | Outsole slip resistance SRA: flat | friction | 0.35 | ≥ 0.32 |
| | Outsole slip resistance SRB: heel | friction | 0.13 | ≥ 0.13 |
| | Outsole slip resistance SRB: flat | friction | 0.19 | ≥ 0.18 |
| | Antistatic value | MegaOhm | 163.9 | 0.1 - 1000 |
| | ESD value | MegaOhm | NA | 0.1 - 100 |
| | Heel energy absorption | J | 34 | ≥ 20 |
| Toecap | Impact resistance toecap (clearance after impact 100J) | mm | NA | ≥ 14 |
| | Compression resistance toecap (clearance after compression 10kN) | mm | NA | ≥ 14 |
| | Impact resistance toecap (clearance after impact 200J) | mm | NA | ≥ 14 |
| | Compression resistance toecap (clearance after compression 15kN) | mm | NA | ≥ 14 |

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size:
41

**SAFETY
JOGGER**
WORKS

INDUSTRIAL PROFESSIONAL TACTICAL

www.pls-shop.co.uk

PLS

ENGINEERED
IN EUROPE