

SAFETY JOGGER

INDUSTRIAL

LADIES

BESTLADY S3

Classic, mid-cut safety shoe with a female touch

Upper	Baku Action Leather
Outsole	PU/PU
Toecap	Steel
Midssole	Steel
Lining	Mesh
Footbed	SJ foam footbed
Safety category	EN ISO 20345 - S3 / SRC
Sample weight	0.520 gr.
Size range	EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 / CM 23.0-27.0



217



S3
S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



SRC SLIP RESISTANCE
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



OIL & FUEL RESISTANT
The outsole is resistant against oil and fuel.



HEEL ENERGY ABSORPTION
Heel energy absorption reduces the impact of jumps or running on the body of the wearer.



STEEL TOECAP
Robust metal support to protect the feet of the wearer against falling or rolling objects.



STEEL MIDSOLE
Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.

SAFETY JOGGER

INDUSTRIAL

LADIES

BESTLADY S3

Industries:

Automotive, Catering, Chemical, Cleaning, Construction, Food & beverages, Industry, Logistics, Mining, Oil & Gas

Environments:

Dry environment, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.



	Description	Measure unit	Result	EN ISO 20345
Upper	Baku Action Leather			
	Upper: permeability to water vapor	mg/cm ² /h	1.6	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	22.9	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	60.5	≥ 2
	Lining: water vapor coefficient	mg/cm ²	484.1	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm ³	29.1	≤ 150
	Outsole slip resistance SRA: heel	friction	0.38	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.38	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.16	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.19	≥ 0.18
	Antistatic value	MegaOhm	120.7	0.1 - 1000
	ESD value	MegaOhm	NA	0.1 - 100
	Heel energy absorption	J	27	≥ 20
Toecap	Steel			
	Impact resistance toecap (clearance after impact 100J)	mm	NA	≥ 13
	Compression resistance toecap (clearance after compression 10kN)	mm	NA	≥ 13
	Impact resistance toecap (clearance after impact 200J)	mm	15.0	≥ 13
	Compression resistance toecap (clearance after compression 15kN)	mm	16.0	≥ 13

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size:
38

**SAFETY
JOGGER**
WORKS

INDUSTRIAL PROFESSIONAL TACTICAL

www.pls-shop.co.uk

PLS

ENGINEERED
IN EUROPE