SAFETY JOGGER
INDUSTRIAL

Medium

BESTRUN2 S3

All features of the original Bestrun in an updated design

Upper	Barton Action Leather
Lining	Mesh
Footbed	SJ foam footbed
Midsole	Steel
Outsole	PU/PU
Toecap	Steel
Safety standard	S3 / SRC
Size range	EU 36-47 / UK 3.5-12.0 US 4.0-13.0 / CM 23.5-31.0
Sample weight	0.602 gr.
Norms	EN ISO 20345:2011 ASTM F2413:2018

217

DGUV BGR 191
These shoes are suitable for orthopedic insoles and orthopedic alterations. Certified according to BGR 191.

SJ Flex
Metalfree puncture resistant material, which is lighter and more flexible than steel. The material is not thermal conductive. Covers 100% of the surface of the last bottom.

Steel toecap
Robust metal support to protect the feet of the wearer against falling or rolling objects.

Steel midsole
Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetating the outsole.

Breathable leather upper
Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.

SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.

SAFETY JOGGER WORKS
Solutions for every workplace
INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP
ENGINEERED IN EUROPE
www.safetyjogger.com
www.pls-shop.co.uk

Industries:
Automotive, Catering, Chemical, Cleaning, Construction, Food & beverages, Logistics, Oil & Gas, Industry

Environments:
Dry environment, Uneven surfaces, Wet environment

Maintenance instructions:
To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	**Barton Action Leather**			
	Upper: permeability to water vapor	mg/cm²/h	2.2	≥ 0.8
	Upper: water vapor coefficient	mg/cm²	25.0	≥ 15
Lining	**Mesh**			
	Lining: permeability to water vapor	mg/cm²/h	67.6	≥ 2
	Lining: water vapor coefficient	mg/cm²	541	≥ 20
Footbed	**SJ foam footbed**			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	**PU/PU**			
	Outsole abrasion resistance (volume loss)	mm³	68.5	≤ 150
	Outsole slip resistance SRA: heel	friction	0.36	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.38	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.13	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	129.3	0.1 - 1000
	ESD value	MegaOhm	NA	0.1 - 100
	Heel energy absorption	J	18.5	≥ 20
Toecap	**Steel**			
	Impact resistance toecap (clearance after impact 100J)	mm	NA	NA
	Compression resistance toecap (clearance after compression 10kN)	mm	NA	NA
	Impact resistance toecap (clearance after impact 200J)	mm	20.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	18.5	≥ 14

Sample size: 41

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

SAFETY JOGGER WORKS
Solutions for every workplace
INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP
ENGINEERED IN EUROPE
www.safetyjogger.com
www.pls-shop.co.uk