

SAFETY JOGGER

INDUSTRIAL



LADIES

BOTANIC S1P

Mid-cut, elegant safety shoe with a female touch

Upper	Suede Leather
Outsole	PU/PU
Toecap	Steel
Midsole	Steel
Lining	Cotton
Footbed	SJ foam footbed
Safety category	EN ISO 20345 - S1P / SRC
Sample weight	0.503 gr.
Size range	EU 35-42 / UK 3.0-8.0 / US 5.5-10.5 / CM 23.0-27.0




S1P

You work in dry environments, no risk of water/liquid sprays, and you need protection for your toes, protection against perforation, and a good breathability? Then you need S1P safety footwear.



STEEL TOECAP

Robust metal support to protect the feet of the wearer against falling or rolling objects.



STEEL MIDSOLE

Puncture resistant steel midsoles are made from stainless or coated steel and prevent sharp objects from penetrating the outsole.



SRC SLIP RESISTANCE

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



ANTISTATIC

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm



BREATHABLE LEATHER UPPER

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.

SAFETY JOGGER
WORKS

INDUSTRIAL PROFESSIONAL TACTICAL

www.pls-shop.co.uk

PLS

ENGINEERED
IN EUROPE

SAFETY JOGGER

INDUSTRIAL



LADIES

BOTANIC S1P

Industries:

Automotive, Chemical, Cleaning, Construction, Food & beverages, Industry, Logistics

Environments:

Dry environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.



	Description	Measure unit	Result	EN ISO 20345
Upper	Suede Leather			
	Upper: permeability to water vapor	mg/cm ² /h	6.9	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	61.1	≥ 15
Lining	Cotton			
	Lining: permeability to water vapor	mg/cm ² /h	60.5	≥ 2
	Lining: water vapor coefficient	mg/cm ²	484.1	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm ³	29.1	≤ 150
	Outsole slip resistance SRA: heel	friction	0.40	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.39	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.15	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.20	≥ 0.18
	Antistatic value	MegaOhm	189.9	0.1 - 1000
	ESD value	MegaOhm	NA	0.1 - 100
	Heel energy absorption	J	27	≥ 20
Toecap	Steel			
	Impact resistance toecap (clearance after impact 100J)	mm	NA	≥ 13
	Compression resistance toecap (clearance after compression 10kN)	mm	NA	≥ 13
	Impact resistance toecap (clearance after impact 200J)	mm	14.0	≥ 13
	Compression resistance toecap (clearance after compression 15kN)	mm	14.5	≥ 13

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size:
37

**SAFETY
JOGGER**
WORKS

INDUSTRIAL PROFESSIONAL TACTICAL

www.pls-shop.co.uk

PLS

ENGINEERED
IN EUROPE