

SAFETY JOGGER

INDUSTRIAL

FOOD

CORTADO SB

Fashionable safety clog with backstrap

Upper	Nappa Action Leather
Outsole	PU/PU
Toecap	Steel
Midsole	N/A
Lining	Mesh
Footbed	SJ Latex M2223
Safety category	EN ISO 20345 - SB / SRC
Sample weight	0.510 gr.
Size range	EU 35-47 / UK 3.0-12.0 / US 3.0-13.0 / CM 23.0-31.0



STEEL TOECAP

Robust metal support to protect the feet of the wearer against falling or rolling objects.




SRC SLIP RESISTANCE

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



OIL & FUEL RESISTANT

The outsole is resistant against oil and fuel.



HEEL ENERGY ABSORPTION

Heel energy absorption reduces the impact of jumps or running on the body of the wearer.



BREATHABLE LEATHER UPPER

Natural leather provides a high degree of wearer comfort combined with durability in versatile applications.



ANTISTATIC

Antistatic footwear prevents build-up of static electrical charges and ensures that they are discharged effectively. Volume resistance between 100 KiloOhm and 1 GigaOhm

SAFETY JOGGER

INDUSTRIAL

FOOD

CORTADO SB

Industries:

Catering, Chemical, Food & beverages, Medical

Environments:

Dry environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Nappa Action Leather			
	Upper: permeability to water vapor	mg/cm ² /h	5.1	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	46	≥ 15
Lining	Mesh			
	Lining: permeability to water vapor	mg/cm ² /h	28.9	≥ 2
	Lining: water vapor coefficient	mg/cm ²	231.1	≥ 20
Footbed	SJ Latex M2223			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm ³	51.7	≤ 150
	Outsole slip resistance SRA: heel	friction	0.31	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.32	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.16	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	NA	0.1 - 1000
	ESD value	MegaOhm	NA	0.1 - 100
	Heel energy absorption	J	NA	≥ 20
Toecap	Steel			
	Impact resistance toecap (clearance after impact 100J)	mm	NA	≥ 14
	Compression resistance toecap (clearance after compression 10kN)	mm	NA	≥ 14
	Impact resistance toecap (clearance after impact 200J)	mm	17.0	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	19.5	≥ 14

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size:
41