

# SAFETY JOGGER

## INDUSTRIAL



SPORTS

## SPEEDY S3

Fashionable mid-cut safety shoe for active professional

Upper	Nubuck Action Leather
Outsole	PU/Rubber
Toecap	Composite
Midsole	Anti-puncture Textile
Lining	3D-Mesh
Footbed	SJ foam footbed
Safety category	EN ISO 20345 - S3 / SRC, HRO
Sample weight	0.640 gr.
Size range	EU 36-47 / UK 3.5-12.0 / US 4.0-13.0 / CM 23.5-31.0



094



### SJ FLEX

Metalfree puncture resistant material, which is lighter and more flexible than steel. The material is not thermal conductive. Covers 100% of the surface of the last bottom.



### SRC SLIP RESISTANCE

Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.



### HEAT RESISTANT OUTSOLE (HRO)

The outsole resists high temperatures up to 300°C.



### COMPOSITE TOECAP

Metalfree and lightweight, no thermal or electrical conductivity



### SPORTS

## SPEEDY S3

### Industries:

Automotive, Cleaning, Construction, Industry, Logistics

### Environments:

Dry environment, Warm surfaces, Wet environment

### Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
<b>Upper</b>	<b>Nubuck Action Leather</b>			
	Upper: permeability to water vapor	mg/cm <sup>2</sup> /h	3.9	≥ 0.8
	Upper: water vapor coefficient	mg/cm <sup>2</sup>	38.4	≥ 15
<b>Lining</b>	<b>3D-Mesh</b>			
	Lining: permeability to water vapor	mg/cm <sup>2</sup> /h	50.8	≥ 2
	Lining: water vapor coefficient	mg/cm <sup>2</sup>	406.9	≥ 20
<b>Footbed</b>	<b>SJ foam footbed</b>			
	Footbed: abrasion resistance	cycles	400	≥ 400
<b>Outsole</b>	<b>PU/Rubber</b>			
	Outsole abrasion resistance (volume loss)	mm <sup>3</sup>	40	≤ 150
	Outsole slip resistance SRA: heel	friction	0.53	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.50	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.18	≥ 0.18
	Antistatic value	MegaOhm	0.32	0.1 - 1000
	ESD value	MegaOhm	NA	0.1 - 100
	Heel energy absorption	J	30	≥ 20
<b>Toecap</b>	<b>Composite</b>			
	Impact resistance toecap (clearance after impact 100J)	mm	NA	≥ 14
	Compression resistance toecap (clearance after compression 10kN)	mm	NA	≥ 14
	Impact resistance toecap (clearance after impact 200J)	mm	17.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	21.5	≥ 14

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

Sample size:  
41