

Medium

X1100N S3

Mid-cut leather safety shoe for protection in style

Upper	Nappa Action Leather
Lining	Cambrella
Footbed	SJ foam footbed
Midsole	Anti-puncture Textile
Outsole	PU/PU
Toecap	Composite
Safety standard	S3 / SRC
Size range	EU 5H-13 / UK 5.0-12.0 US 5.5-13.0 / CM 25.0-31.0
Sample weight	0.676 gr.
Norms	EN ISO 20345:2011 ASTM F2413:2018




BLK



S3
S3 safety shoes are suitable for work in an environment with high humidity and presence of oil or hydrocarbons. These shoes also protect against perforation risk of the sole, and foot crushing.



SRC slip resistance
Slip resistant soles are one of the most important features of safety and occupational footwear. SRC slip resistant soles pass both SRA and SRB slip resistant tests, they are tested on both steel and ceramic surfaces.




Metal free
Metal free safety shoes are in general lighter than regular safety shoes. They are also very beneficial for professionals who have to pass through metal detectors several times a day.



SJ Flex
Metalfree puncture resistant material, which is lighter and more flexible than steel. The material is not thermal conductive. Covers 100% of the surface of the last bottom.



Composite toecap
Metalfree and lightweight, no thermal or electrical conductivity



Oil & fuel resistant
The outsole is resistant against oil and fuel.

Industries:

Automotive, Cleaning, Construction, Logistics, Mining, Oil & Gas, Industry, Uniform

Environments:

Dry environment, Muddy environment, Uneven surfaces, Wet environment

Maintenance instructions:

To extend the life of your shoes, we recommend to clean them regularly and to protect them with adequate products. Do not dry your shoes on a radiator, nor nearby a heat source.

	Description	Measure unit	Result	EN ISO 20345
Upper	Nappa Action Leather			
	Upper: permeability to water vapor	mg/cm ² /h	1.8	≥ 0.8
	Upper: water vapor coefficient	mg/cm ²	19	≥ 15
Lining	Cambrella			
	Lining: permeability to water vapor	mg/cm ² /h	39.2	≥ 2
	Lining: water vapor coefficient	mg/cm ²	314.3	≥ 20
Footbed	SJ foam footbed			
	Footbed: abrasion resistance	cycles	400	≥ 400
Outsole	PU/PU			
	Outsole abrasion resistance (volume loss)	mm ³	110	≤ 150
	Outsole slip resistance SRA: heel	friction	0.36	≥ 0.28
	Outsole slip resistance SRA: flat	friction	0.33	≥ 0.32
	Outsole slip resistance SRB: heel	friction	0.14	≥ 0.13
	Outsole slip resistance SRB: flat	friction	0.19	≥ 0.18
	Antistatic value	MegaOhm	265	0.1 - 1000
	ESD value	MegaOhm	N/A	0.1 - 100
	Heel energy absorption	J	24	≥ 20
Toecap	Composite			
	Impact resistance toecap (clearance after impact 100J)	mm	N/A	NA
	Compression resistance toecap (clearance after compression 10kN)	mm	N/A	NA
	Impact resistance toecap (clearance after impact 200J)	mm	14.5	≥ 14
	Compression resistance toecap (clearance after compression 15kN)	mm	22	≥ 14

Sample size: 42

Our shoes are constantly evolving, the technical data above may change. All product names and brand Safety Jogger, are registered and may not be used or reproduced in any format, without written consent from us.

**Solutions for every workplace**

INDUSTRIAL PROFESSIONAL TACTICAL TIGER GRIP

www.pls-shop.co.uk**ENGINEERED
IN EUROPE**www.safetyjogger.com